TENT COOPERATION TRE TY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Commissioner **US Department of Commerce** United States Patent and Trademark Office, PCT 2011 South Clark Place Room CP2/5C24 Arlington, VA 22202 FTATS-UNIS D'AMERIQUE

n its capacity as elected Office

Date of mailing (day/month/year)	II ETATS-UNIS D'AIVIENIQU		
08 November 2000 (08.11.00)	in its capacity as e		
International application No.	Applicant's or agent's file reference		
PCT/GR00/01082	KWN 7250 01/H		

PC1/GB00/01082 International filing date (day/month/year) 23 March 2000 (23.03.00)

KWN 7250-01/H Priority date (day/month/year) 25 March 1999 (25.03.99)

Applicant

NORTH, John, Herbert

1.	The designated Office is hereby notified of its election made:
	X in the demand filed with the International Preliminary Examining Authority on:
	22 September 2000 (22.09.00)
	in a notice effecting later election filed with the International Bureau on:
2.	The election X was was not
	made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).
	•

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

Olivia TEFY

Telephone No.: (41-22) 338.83.38

Facsimile No.: (41-22) 740.14.35


PATENT COOPERATION TREATY

	From the INTERNATIONAL BUREAU			
PCT	To:			
NOTIFICATION RELATING TO PRIORITY CLAIM				
(PCT Rules 26bis.1 and 26bis.2 and Administrative Instructions, Sections 402 and 409)	KEITH W. NASH & CO. 90-92 Regent Street Cambridge CB2 1DP ROYAUME-UNI			
Date of mailing (day/month/year) 19 July 2000 (19.07.00)				
Applicant's or agent's file reference KWN 7250-01/H	IMPORTANT NOTIFICATION			
International application No. PCT/GB00/01082	International filing date (day/month/year) 23 March 2000 (23.03.00)			
Applicant				
NORTH, John, Herbert				
The applicant is hereby notified of the following in respect of the	e priority claim(s) made in the international application.			
1. X Correction of priority claim. In accordance with the applicant's notice received on: 30 May 2000 (30.05.00), the following priority claim has been corrected to read as follows: GB 29 April 1999 (29.04.99) 9909836.0 even though the indication of the number of the earlier application is missing. even though the following indication in the priority claim is not the same as the corresponding indication appear in the priority document: 2. Addition of priority claim. In accordance with the applicant's notice received on: , the following priority claim has been added: even though the indication of the number of the earlier application is missing. even though the following indication in the priority claim is not the same as the corresponding indication appear in the priority document: 3. As a result of the correction and/or addition of (a) priority claim(s) under items 1 and/or 2, the (earliest) priority date in the applicant failed to respond to the Invitation under Rule 26bis.2(a) (Form PCT/IB/316) within the prescribed time I have applicant's notice was received after the expiration of the prescribed time limit under Rule 26bis.1(a). The applicant's notice was received after the expiration of the prescribed time limit under Rule 26bis.1(a). The applicant failed to correct the priority claim so as to comply with the requirements of Rule 4.10. The applicant may, before the technical preparations for international publication have been completed and subject payment of a fee, request the International Bureau to publish, together with the international application, information concerning the priority claim. See Rule 26bis.2(e) and the PCT Applicant's Guide, Volume I, Annex B2(IB).				
 In case where multiple priorities have been claimed, the second of this notification has been sent to the receiving Offic X to the International Searching Authority (where the intern X the designated Offices (which have already been notified 	ce and national search report has not yet been issued).			
The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Authorized officer Lazar Joseph Panakal				
Facsimile No. (41-22) 740.14.35	Telephone No. (41-22) 338.83.38			

PATENT COOPERATION TREATY

From the INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY





PCT

NOTIFICATION OF TRANSMITTAL OF THE INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Rule 71.1)

Date of mailing (day/month/year)

30.05.2001

Applicant's or agent's file reference . C725.01/H

0/23.01/11

PCT/GB00/01082

International filing date (day/month/year)

23/03/2000

Priority date (day/month/year)

25/03/1999

Applicant

NORTH, John Herbert

International application No.

- 1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
- 2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
- 3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/

European Patent Office D-80298 Munich

Tel. +49 89 2399 - 0 Tx: 523656 epmu d

Fax: +49 89 2399 - 4465

Authorized officer

Marra, E

Tel.+49 89 2399-7235



PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's	or age	ent's file reference		See	Notification of Transmittal of International
C725.01			FOR FURTHER ACTION		iminary Examination Report (Form PCT/IPEA/416)
Internation	al appl	ication No.	International filing date (day/mor	th/year)	Priority date (day/month/year)
PCT/GB	00/01	082	23/03/2000		25/03/1999
Internation D06F35/		ent Classification (IPC) or r	national classification and IPC		
Applicant	lohr	n Herbert			
NONTH,	30111	Therbert			
			mination report has been prepar according to Article 36.	ed by th	is International Preliminary Examining Author
2. This	REPC	ORT consists of a total of	of 6 sheets, including this cover	sheet.	
t (een a see R	mended and are the b	asis for this report and/or sheets 607 of the Administrative Instruc	contain	cription, claims and/or drawings which have ning rectifications made before this Authority nder the PCT).
3. This	report ⊠	contains indications re	lating to the following items:		
11		•			
Ш			·	nventive	e step and industrial applicability
IV	⊠			4.	
V	×		under Article 35(2) with regard t tions suporting such statement	onoveit	y, inventive step or industrial applicability;
VI		Certain documents c	ited		
VII	\boxtimes	Certain defects in the	international application		
VIII	Ø	Certain observations	on the international application		
Date of sul	omissio	on of the demand	Date	of comple	etion of this report
22/09/20	000		30.05	2001	
		g address of the internation	nal Autho	rized offic	COT JUNEOUS MAI
<u></u>	Euro D-8	opean Patent Office 0298 Munich		as, K	A STREET OF THE
	Tel. +49 89 2399 - 0 Tx: 523656 epmu d				140 00 0000 0000



International application No. PCT/GB00/01082

I. Bas	is of	the	report
--------	-------	-----	--------

1.	With regard to the elements of the international application (Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)): Description, pages:							
	1-2	1	as originally filed					
	Cla	ims, No.:						
	1-5	0	as received on	14/04/2001	with letter of	10/04/2001		
	Dra	awings, sheets:						
	1/1	0-10/10	as originally filed					
2.			guage, all the elements mark international application was					
	The	ese elements were a	available or furnished to this a	Authority in the f	ollowing language:	, which is:		
		the language of a	translation furnished for the p	ourposes of the i	nternational search	(under Rule 23.1(b)).		
		the language of pu	ublication of the international	application (und	er Rule 48.3(b)).			
		the language of a 55.2 and/or 55.3).	translation furnished for the p	ourposes of inter	national preliminary	examination (under Rule		
3.			eleotide and/or amino acid s y examination was carried or					
		contained in the in	ternational application in writ	ten form.				
		filed together with	the international application i	in computer read	lable form.			
		furnished subsequently to this Authority in written form.						
		furnished subsequ	ently to this Authority in com	puter readable fo	orm.			
☐ The statement that the subsequently furnished written sequence listing does not go beyond the international application as filed has been furnished.						o beyond the disclosure in		
		The statement that listing has been fu	t the information recorded in rnished.	computer readal	ble form is identical	to the written sequence		
4.	The	amendments have	e resulted in the cancellation	of:				
		the description,	pages:					
		the claims,	Nos.:					



International application No. PCT/GB00/01082

		the drawings,	sheets:							
5.	☒	This report has been considered to go bey						ıot been m	ade, since	they have bee
		(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to report.) see separate sheet								annexed to this
6.	Add	litional observations, i	f necessar	ry:						
IV	Lac	ck of unity of invention	on							
		esponse to the invitation		ict or pav	additio	nal fees the a	pplicant ha	as:		•
••		restricted the claims.		,			•			
		paid additional fees.								
		paid additional fees u	ınder prote	est.						
		neither restricted nor	paid addit	tional fees	3.					
2.		This Authority found that the requirement of unity of invention is not complied and chose, according to Rule 68.1, not to invite the applicant to restrict or pay additional fees.								
3.	This	s Authority considers t	hat the red	quirement	of unity	y of invention	in accorda	ince with R	ules 13.1,	, 13.2 and 13.3
		complied with.								
	×	not complied with for see separate sheet	the follow	ing reaso	ns:					
4.		nsequently, the followin mination in establishin			nationa	l application w	vere the su	ibject of int	ernational	I preliminary
		all parts.								
	×	the parts relating to c	laims Nos	. 1-44.						
V.		soned statement un tions and explanatio					y, inventiv	e step or	industrial	l applicability;
1.	Stat	tement								
	Nov	reity (N)	Yes: No:	Claims Claims	1-44					
	Inve	entive step (IS)	Yes: No:	Claims Claims	1-44					



International application No. PCT/GB00/01082

Industrial applicability (IA)

Yes:

Claims 1-44

No:

Claims

2. Citations and explanations see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted: see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made: see separate sheet

Ad Section IV

The elliptical capsule disclosed in claims 1 to 44 is not mentioned in the claims 45 to 50.

Therefore, the claims are not so linked as to form a single general inventive concept (Rule 13.1 PCT).

Section V

Claims 1 and 42

GB 1 069 569 A describes a washing process performed in a process vessel for textile fabrics comprising a washing operation at elevated pressure.

It is the object of the present invention to provide apparatus and a method of washing articles that can be used in a shorter time-scale and with reduced energy requirements and which can be used with minor modification for dry-cleaning articles using an appropriate dry-cleaning solvent.

This object is achieved through a machine according to claim 1 and a method according to claim 42, wherein a washing operation at elevated pressure takes place in an elliptical rotatable capsule.

None of the documents of the international search report discloses such a solution.

Claims 1 and 42 therefore fulfil the requirements of Articles 33(2) and 33(3) PCT.

Claims 2 to 41, 43, 44

Claims 2 to 41, 43, 44 disclosing modifications of the inventive idea embodied in claims 1 and 42, also meet the requirements of Articles 33(2) and 33(3) PCT.

Ad section VII



- 1. Independent claims are not in the two-part form in accordance with Rule 6.3(b) PCT.
- 2. The features of the claims are not provided with reference signs placed in parentheses (Rule 6.2(b) PCT).
- 3. Contrary to the requirements of Rule 5.1(a)(ii) PCT, the relevant background art disclosed in the document GB 1 069 569 A is not mentioned in the description, nor is this document identified therein.

Ad section VIII

The unit "psi" used in the description should have been replaced by the appropriate SI unit. The present expression should have been retained in parentheses after the replacement expression.

1

C725.01/H

CLAIMS

- 1. A machine for washing and/or cleaning articles, which comprises a sealable enclosure for containing the articles to which cleaning liquid is to be supplied, characterised in that the cleaning liquid is heated to a high temperature and forced into the enclosure under high pressure as finely dispersed or diffused droplets forming a mist or vapour so that a pressure greater than atmospheric is maintained in the enclosure to force the cleaning liquid into at least the surface if not through and into the very structure of the material from which the articles are formed, so as to assist the cleaning process, and wherein the enclosure is in the form of an elliptical capsule mounted for rotation about an axis through the mid-point of its longer axis, so that articles located therein will tend to fall from one end to the other as the capsule is rotated thereby to assist in the mixing of the liquids introduced into the capsule.
- A machine as claimed in claim 1, wherein the cleaning liquid is removed from the
 articles and the interior of the enclosure by means of a suction pump and replaced by
 clean liquid for rinsing, and if desired also heated to higher than ambient
 temperatures.
- 3. A machine as claimed in claim 2, wherein the liquid supplied for rinsing is also at higher than atmospheric pressure.
- 4. A machine as claimed in claim 2 or 3, wherein the rinsing liquid is also heated above ambient temperature.
- 5. A machine as claimed in either of claims 3 or 4, wherein the rinsing liquid is removed from the enclosure by suction.

- 6. A machine as claimed in any of claims 1 to 5, wherein means is provided for extracting residual moisture from the articles in the form of a suction pump, wherein during a drying cycle following washing and/or a rinsing cycle suction is employed to reduce the pressure on the downstream side of the enclosure substantially below atmospheric, so that evaporative drying of moisture remaining on or in the material from which the articles are formed, occurs.
- 7. A machine as claimed in claim 6, wherein the vapour laden air produced by the evaporation is removed from the enclosure by the scavenging action of the air being drawn from the enclosure under the suction.
- 8. A machine as claimed in any of claims 1 to 7, wherein the enclosure comprises a rotatable drum, with a drive means for rotating the drum when in use and inlet and outlet means which permit relative movement to enable liquid and air to be supplied, to and drawn off therefrom, whilst the drum is rotating.
- 9. A machine as claimed in any of claims 1 to 7, wherein the enclosure comprises a housing within which a rotatable drum is mounted and the drum is adapted by means of openings to permit air and liquid to be forced axially and/or radially therethrough.
- 10. A machine as claimed in claim 9, wherein the openings comprise a large number of small apertures such as perforations in the wall of the drum.
- 11. A machine as claimed in claims 9 and 10, wherein the air and liquid mixture may be forced into the drum in a radial sense from the space around the drum within the housing, and be collected and conveyed away from the drum via a central porous or apertured hollow sleeve, mounted axially and centrally within the drum.
- 12. A machine as claimed in any of claims 9 to 11, wherein the housing forms part of the drum and rotate therewith, or is stationary so as to simplify the air and liquid supply to, and drainage from, the drum.

- 13. A machine as claimed in claim 1, wherein a reservoir is provided for containing a drycleaning fluid and valves and pumps are controlled by a computer to introduce a given value of the fluid into the under positive pressure after articles have been inserted, and the enclosure sealed to atmosphere and after rotation and thoroughly mixing the article, and the fluid, a suction pump is operated to evacuate the enclosure and remove the dry cleaning fluid and vapour therefrom.
- 14. A machine as claimed in any of claims 1 to 13, wherein the above atmospheric air pressure is obtained using an impeller, or turbine, or a centrifugal air pump.
- 15. A machine as claimed in any of claims 1 to 14, wherein the suction to produce depressed pressures below atmospheric is obtained using a venturi vacuum pump.
- 16. A machine as claimed in claim 15, wherein the venturi pump is a dual conical venturi jet high vacuum pump capable of generating a suction equivalent to 760mm Hg.
- 17. A machine as claimed in any of claims 1 to 16, wherein a filter is provided at the inlet to the enclosure and liquid is finely dispersed and/or diffused on entry into the enclosure by forcing it therethrough.
- 18. A machine as claimed in any of claims 1 to 17, wherein means is provided to mix the liquid with air at elevated pressure, and optionally desired elevated temperature, before being forced under pressure through the inlet filter.
- 19. A machine as claimed in either of claims 17 or 18, wherein the filter is a fine mesh filter.
- 20. A machine as claimed in claim 1, wherein the enclosure is in the form of an elliptical capsule mounted for rotation about an axis through the mid-point of the longer axis perpendicular to the latter and comprising a diameter of the cylindrical mid-region of

the capsule, so that articles located therein will tend to fall from one end to the other as the capsule is rotated and thereby assist in the mixing of the liquids introduced into the capsule during the washing or cleaning process and to agitate the articles excessively during the drying cycle to further assist in removing moisture therefrom.

- 21. A machine as claimed in claim 20, in which the capsule is to be loaded and unloaded through a circular opening in the front wall of a rectangular housing within which the capsule is located for rotation, and wherein the opening in the front housing wall is normally closed by a hinged circular door, the front opening (and in consequence the door also), is arranged coaxially relative to the axis of rotation of the capsule, and the capsule includes a circular opening which aligns with the circular front housing opening, and an annular seal is provided between the two openings to enable a positive pressure to be maintained in the capsule after the door has been closed.
- 22. A machine as claimed in claim 21, wherein a double door assembly is provided one closing an opening in the capsule wall and the other the opening in the front wall of the housing.
- 23. A machine as claimed in claim 22, wherein a seal is provided around each said door to seal it against the opening in the capsule wall, or the opening in the front housing wall, respectively.
- 24. A machine as claimed in any of claims 20 to 23, wherein valve means is provided to control the admission of liquid and air to the capsule after the openings have been sealingly closed.
- 25. A machine as claimed in claim 24, wherein the valve means comprises a solenoid valve.
- 26. A machine as claimed in any of claims 20 to 25, wherein the capsule is mounted for rotation by two rotary support bearing assemblies, one surrounding the loading and

unloading opening and the other attached to a diametrically opposite region of the cylindrical wall of the mid-region of the capsule coaxial with the first bearing assembly.

- 27. A machine as claimed in claim 26, wherein the second bearing assembly surrounds a circular region in the capsule wall opposite to the loading and unloading opening, and concentric pipe means having a rotary seal with the wall of the capsule, enables the capsule to rotate whilst still being connected to the liquid and air supplies and also allows liquid and air to enter the capsule whilst the latter rotates.
- 28. A machine as claimed in claim 27, wherein the pipe means communicates with one or more fine mesh filters to disperse and diffuse incoming high pressure liquid and air into a fine mist.
- 29. A machine as claimed in any of claims 24 to 28, wherein the valve means controlling the passage of liquid and air into the capsule is arranged adjacent the pipe means where it extends through the capsule wall and is attached to, or forms part, of the capsule wall.
- 30. A machine as claimed in claim 29, wherein the pipe means and valve is surrounded by and extends axially through a hollow cylindrical drive shaft carrying a large diameter pulley which shaft extends through a support bearing assembly at the rear of the capsule and is joined to the capsule wall, and an electric motor, whose output shaft carries a complementary pulley aligned with the first mentioned pulley, allows drive to be transmitted to the drive shaft from the motor via a drive band, to rotate the capsule about the support bearing axis.
- 31. A machine as claimed in claim 30, wherein the bearing assembly is a so-called split bearing and is mounted on a sub-frame within the housing.

- 32. A machine as claimed in any of claims 21 to 31, wherein the opposite ends of the capsule include sieve-type filters and the pipe means delivers liquid and air to the two filters to enter the interior of the capsule from opposite ends thereof.
- 33. A machine as claimed in any of claims 21 to 31, wherein a hollow cylindrical sleeve extends across the interior of the capsule coaxial with the aligned support bearing axes which define the axis of rotation of the capsule, and the sleeve wall is perforated with tiny apertures through which the liquid and air exit into the interior of the capsule as a fine mist diffused by the tiny perforations, which form a cylindrical fine mesh sieve type filter.
- 34. A machine as claimed in claim 32 or 33, wherein the fine mesh filter allows the incoming pressurized liquid and air to diffuse into the articles and produce a fast gaseous reaction inside the capsule due the liquid gaining heat energy by virtue of the liquid being forced through the plurality of tiny openings making up the filter mesh, so as to produce a sprinkler jet action for the gas-liquid mixture.
- 35. A machine for washing as claimed in any of claims 21 to 34, wherein a heater is provided to heat the water to boiling point so that at least part of the liquid entering the capsule is in the form of steam vapour.
- 36. A machine as claimed in any of claims 21 to 35, wherein the shape of the capsule ensures that articles and liquid are tumbled from one end to the other under gravity as the capsule is rotated.
- 37. A machine as claimed in any of claims 1 to 36, wherein the air expands due to its being heated after coming into contact with the steam so that a further increase in pressure within the capsule results causing the detergent suds to more thoroughly permeate the articles particularly where the latter are formed from woven fabric, so further assisting the release of dirt and particles causing stains and marks in the fabric.

- 38. A machine as claimed in any of claims 21 to 37 for washing articles, wherein access to the enclosure is via a top opening, means is provided to extract the liquid and air from the end of the capsule opposite to the end containing the sealable opening through which access can be gained to the interior of the capsule, so that the garments tend to gravitate towards the end opposite to the opening under the suction effect, and in this way the weight of the garments at that end will tend to ensure that the capsule will always come to rest with its end containing the access aperture uppermost and in alignment with an opening in the housing surrounding the capsule which in use will normally be closed by a lid.
- 39. A machine as claimed in any of the preceding claims 2 to 38, wherein the vacuum pump comprises a venturi tube includes a peripheral air duct, set around the outside of the venturi outlet, and this arrangement accelerates with flow, and the venturi tube is connected to a branch inlet at the mid point of a 90 degree radius bend relative to the centreline of the tube o/d to provide a strong vacuum suction, pump delivers water through the venturi supply tube, and an air blower outlet is connected via a pipe to the peripheral air chamber to control the air flow around the venturi, which in turn controls the amount of the suction.
- 40. A machine as claimed in claim 39, wherein an air pressure relief valve is provided which also controls the amount of suction created.
- 41. A machine as claimed in any of claims 21 to 40, wherein the vacuum, the temperature, and the pressure are displayed in an analogue or digital display (preferably an analogue LCD bar display) on the front of the machine housing.
- 42. A method of washing articles using a machine as claimed in any of claims 1 to 41, comprising the steps of:
- inserting an article or articles to be washed, into a sealable capsule,
- sealing the capsule


- introducing a detergent solution at or around boiling point together with steam into the sealed capsule, under a pressure greater than ambient
- rotating the capsule to agitate the article(s) and effect a mixing of the liquid and steam therewith
- pumping the liquid from the capsule after a predetermined time
- introducing clean water into the capsule and further rotating same to rinse the articles
- pumping the rinsing water from the capsule after a predetermined time
- continuing to pump the capsule so as to lower the pressure therein to below atmospheric for a further predetermined period of time to assist in evaporative drying of the article(s) therein
- removing the article(s) after establishing ambient pressure in the capsule.
- 43. A method as claimed in claim 42, wherein the suction pumping of liquids and air is effected using a venturi suction pump.
- 44. A machine as claimed in any of claims 1 to 41 which includes a reservoir of a volatile cleaning fluid such as isopropyl alcohol, means for introducing the fluid into the capsule with one or more items of clothing or the like which are to be dry cleaned, means for sealing the capsule so as to provide a gas-tight compartment, means for rotating the capsule in the range 80-100rpm, prior to unsealing the capsule to remove the clothing or like articles, and suction pump means, particularly a venturi vacuum pump, for extracting vapours and gases left over from the cleaning process.
- 45. A machine for washing articles which comprises a sealable enclosure for containing the articles to which a mixture of detergent and water (washing liquid) is to be supplied, characterised in that the liquid is heated to a high temperature and forced into the enclosure under high pressure so as to form a two phase vapour or mist of finely dispersed or diffused droplets of liquid and steam, and a pressure greater than atmospheric is maintained in the enclosure to force the liquid into at least the surface if not through and into the very structure of the material from which the articles are formed, so as to assist the washing process.

- 46. A machine for washing and/or cleaning articles which comprises a sealable enclosure for containing the articles to which cleaning liquid is to be supplied, characterised in that the cleaning liquid is heated to a high temperature and forced into the enclosure under high pressure as finely dispersed or diffused droplets forming a mist or vapour so that a pressure greater than atmospheric is maintained in the enclosure to force the cleaning liquid into at least the surface if not through and into the very structure of the material from which the articles are formed, so as to assist the cleaning process, wherein the cleaning liquid is removed from the articles and from the interior of the enclosure by means of a suction pump.
- 47. A machine as claimed in claim 46 wherein the suction pump is a venturi pump and water supplied thereto under pressure by a pump (16), and after leaving the venturi pump, the water is conveyed to a sump (150) which includes a return pipe (154 for returning the water to the pump (116).

48. A method of washing articles comprising the steps of:

- inserting an article or articles to be washed into a sealable capsule,
- sealing the capsule, and further characterised by the steps of:-
- introducing a detergent solution at or around boiling point together with steam into the sealed capsule, under a pressure greater than ambient
- rotating the capsule to agitate the article(s) and effect a mixing of the liquid and steam therewith
- pumping the liquid from the capsule after a predetermined time
- introducing clean water into the capsule and further rotating same to rinse the articles
- pumping the rinsing water from the capsule after a predetermined time
- continuing to pump the capsule so as to lower the pressure therein to below atmospheric for a further predetermined period of time to assist in evaporative drying of the article(s) therein, and
- removing the article(s) after establishing ambient pressure in the capsule.

- 49. A method as claimed in claim 48, wherein the suction pumping of liquids and air is effected using a venturi suction pump.
- 50. A method as claimed in claim 48 or 49 wherein the water is mixed with detergent and the mixture is subsequently pressurised to a pressure above ambient prior to being introduced into the capsule.



1. In a machine for washing and/or cleaning articles and which comprises a sealable enclosure for containing the articles to which cleaning liquid is to be supplied, the cleaning liquid is heated to a high temperature and forced into the enclosure under high pressure as finely dispersed or diffused droplets forming a mist or vapour so that a pressure greater than atmospheric is maintained in the enclosure to force the cleaning

liquid into at least the surface if not through and into the very structure of the material

2. In a machine as claimed in claim 1, the cleaning liquid is removed from the articles and the interior of the enclosure by means of a suction pump and replaced by clean liquid for rinsing, and if desired also heated to higher than ambient temperatures.

from which the articles are formed, so as to assist the cleaning process.

- 3. In a machine as claimed in claim 2, the liquid supplied for rinsing is also at higher than atmospheric pressure.
- 4. In a machine as claimed in claim 2 or 3, the rising liquid is also heated above ambient temperature.
- 5. In a machine as claimed in either of claims 3 or 4, the rinsing liquid is removed from the enclosure by suction.
- 6. In a machine as claimed in any of claims 1 to 5, means is provided for extracting residual moisture from the articles in the form of a suction pump, wherein during a drying cycle following washing and/or a rinsing cycle suction is employed to reduce the pressure on the downstream side of the enclosure substantially below atmospheric,

so that evaporative drying of moisture remaining on or in the material from which the articles are formed, occurs.

- 7. In a machine as claimed in claim 6, the vapour laden air produced by the evaporation is removed from the enclosure by the scavenging action of the air being drawn from the enclosure under the suction.
- 8. In a machine as claimed in any of claims 1 to 7, the enclosure comprises a rotatable drum, with a drive means for rotating the drum when in use and inlet and outlet means which permit relative movement to enable liquid and air to be supplied, to and drawn off therefrom, whilst the drum is rotating.
- 9. In a machine as claimed in any of claims 1 to 7, the enclosure comprises a housing within which a rotatable drum is mounted and the drum is adapted by means of openings to permit air and liquid to be forced axially and/or radially therethrough.
- 10. In a machine as claimed in claim 9, the openings comprise a large number of small apertures such as perforations in the wall of the drum.
- 11. In a machine as claimed in claim s9 and 10, the air and liquid mixture may be forced into the drum in a radial sense from the space around the drum within the housing, and be collected and conveyed away from the drum via a central porous or apertured hollow sleeve, mounted axially and centrally within the drum.
- 12. In a machine as claimed in any of claims 9 to 11, the housing forms part of the drum and rotate therewith, or is stationary so as to simplify the air and liquid supply to, and drainage from, the drum.
- 13. In a machine as claimed in claim 1, a reservoir is provided for containing a drycleaning fluid and valves and pumps are controlled by a computer to introduce a given value of the fluid into the under positive pressure after articles have been inserted, and

the enclosure sealed to atmosphere and after rotation and thoroughly mixing the article, and the fluid, a suction pump is operated to evacuate the enclosure and remove the dry cleaning fluid and vapour therefrom.

- 14. In a machine as claimed in any of claims 1 to 13, the above atmospheric air pressure is obtained using an impeller, or turbine, or a centrifugal air pump.
- 15. In a machine as claimed in any of claims 1 to 14, the suction to produce depressed pressures below atmospheric is obtained using a venturi vacuum pump.
- 16. In a machine as claimed in claim 15, the venturi pump is a dual conical venturi jet high vacuum pump capable of generating a suction equivalent to 760mm Hg.
- 17. In a machine as claimed in any of claims 1 to 16, wherein a filter is provided at the inlet to the enclosure and liquid is finely dispersed and/or diffused on entry into the enclosure by forcing it therethrough.
- 18. In a machine as claimed in any of claims 1 to 17, means is provided to mix the liquid with air at elevated pressure, and optionally desired elevated temperature, before being forced under pressure through the inlet filter.
- 19. In a machine as claimed in either of claims 17 or 18, wherein the filter is a fine mesh filter.
- 20. In a machine as claimed in claim 1, the enclosure is in the form of an elliptical capsule mounted for rotation about an axis through the mid-point of the longer axis perpendicular to the latter and comprising a diameter of the cylindrical mid-region of the capsule, so that articles located therein will tend to fall from one end to the other as the capsule is rotated and thereby assist in the mixing of the liquids introduced into the capsule during the washing or cleaning process and to agitate the articles excessively during the drying cycle to further assist in removing moisture therefrom.

- 21. In a machine as claimed in claim 20, in which the capsule is to be loaded and unloaded through a circular opening in the front wall of a rectangular housing within which the capsule is located for rotation, and wherein the opening in the front housing wall is normally closed by a hinged circular door, the front opening (and in consequence the door also), is arranged coaxially relative to the axis of rotation of the capsule, and the capsule includes a circular opening which aligns with the circular front housing opening, and an annular seal is provided between the two openings to enable a positive pressure to be maintained in the capsule after the door has been closed.
- 22. In a machine as claimed in claim 21, a double door assembly is provided one closing an opening in the capsule wall and the other the opening in the front wall of the housing.
- 23. In a machine as claimed in claim 22, a seal is provided around each said door to seal it against the opening in the capsule wall, or the opening in the front housing wall, respectively.
- 24. In machine as claimed in any of claims 20 to 23, valve means is provided to control the admission of liquid and air to the capsule after the openings have been sealingly closed.
- 25. In a machine as claimed in claim 24, the valve means comprises a solenoid valves.
- 26. In a machine as claimed in any of claims 20 to 25, the capsule is mounted for rotation by two rotary support bearing assemblies, one surrounding the loading and unloading opening and the other attached to a diametrically opposite region of the cylindrical wall of the mid-region of the capsule coaxial with the first bearing assembly.
- 27. In a machine as claimed in claim 26, the second bearing assembly surrounds a circular region in the capsule wall opposite to the loading and unloading opening, and concentric pipe means having a rotary seal with the wall of the capsule, enables the

capsule to rotate whilst still being connected to the liquid and air supplies and also allows liquid and air to enter the capsule whilst the latter rotates.

- 28. In a machine as claimed in claim 27, the pipe means communicates with one or more fine mesh filters to disperse and diffuse incoming high pressure liquid and air into a fine mist.
- 29. In a machine as claimed in any of claims 24 to 28, the valve means controlling the passage of liquid and air into the capsule is arranged adjacent the pipe means where it extends through the capsule wall and is attached to, or forms part, of the capsule wall.
- 30. In a machine as claimed in claim 29, the pipe means and valve is surrounded by and extends axially through a hollow cylindrical drive shaft carrying a large diameter pulley which shaft extends through a support bearing assembly at the rear of the capsule and is joined to the capsule wall, and an electric motor, whose output shaft carries a complementary pulley aligned with the first mentioned pulley, allows drive to be transmitted to the drive shaft from the motor via a drive band, to rotate the capsule about the support bearing axis.
- 31. In a machine as claimed in claim 30, the bearing assembly is a so-called split bearing and is mounted on a sub-frame within the housing.
- 32. In a machine as claimed in any of claims 21 to 31, the opposite ends of the capsule include sieve-type filters and the pipe means delivers liquid and air to the two filters to enter the interior of the capsule from opposite ends thereof.
- 33. In a machine as claimed in any of claims 21 to 31, a hollow cylindrical sleeve extends across the interior of the capsule coaxial with the aligned support bearing axes which define the axis of rotation of the capsule, and the sleeve wall is perforated with tiny apertures through which the liquid and air exit into the interior of the capsule as a fine

mist diffused by the tiny perforations, which form a cylindrical fine mesh sieve type filter.

- 34. In a machine as claimed in claim 32 or 33, the fine mesh filter allows the incoming pressurised liquid and air to diffuse into the articles and produce a fast gaseous reaction inside the capsule due the liquid gaining heat energy by virtue of the liquid being forced through the plurality of tiny openings making up the filter mesh, so as to produce a sprinkler jet action for the gas-liquid mixture.
- 35. In a machine for washing as claimed in any of claims 21 to 34, a heater is provided to heat the water to boiling point so that at least part of the liquid entering the capsule is in the form of steam vapour.
- 36. In a machine as claimed in any of claims 21 to 35, wherein the shape of the capsule ensures that articles and liquid are tumbled from one end to the other under gravity as the capsule is rotated.
- 37. In a machine as claimed in any of claims 1 to 36, wherein the air expands due to its being heated after coming into contact with the steam so that a further increase in pressure within the capsule results causing the detergent suds to more thoroughly permeate the articles particularly where the latter are formed from woven fabric, so further assisting the release of dirt and particles causing stains and marks in the fabric.
- 38. In a machine as claimed in any of claims 21 to 37 for washing articles, wherein access to the enclosure is via a top opening, means is provided to extract the liquid and air from the end of the capsule opposite to the end containing the sealable opening through which access can be gained to the interior of the capsule, so that the garments tend to gravitate towards the end opposite to the opening under the suction effect, and in this way the weight of the garments at that end will tend to ensure that the capsule will always come to rest with its end containing the access aperture uppermost and in

alignment with an opening in the housing surrounding the capsule which in use will normally be closed by a lid.

- 39. A machine as claimed in any of the preceding claims 2 to 38, wherein the vacuum pump comprises a venturi tube includes a peripheral air duct, set around the outside of the venturi outlet, and this arrangement accelerates with flow, and the venturi tube is connected to a branch inlet at the mid point of a 90 degree radius bend relative to the centreline of the tube o/d to provide a strong vacuum suction, pump delivers water through the venturi supply tube, and an air blower outlet is connected via a pipe to the peripheral air chamber to control the air flow around the venturi, which in turn controls the amount of the suction.
- 40. A machine as claimed in claim 39, wherein an air pressure relief valve is provided which also controls the amount of suction created.
- 41. A machine as claimed in any of claims 21 to 40, wherein the vacuum, the temperature, and the pressure are displayed in an analogue or digital display (preferably an analogue LCD bar display) on the front of the machine housing.
- 42. A method of washing articles using a machine as claimed in any of claims 1 to 41, comprising the steps of:
- inserting an article or articles to be washed, into a sealable capsule,
- sealing the capsule
- introducing a detergent solution at or around boiling point together with steam into the sealed capsule, under a pressure greater than ambient
- rotating the capsule to agitate the article(s) and effect a mixing of the liquid and steam therewith
- pumping the liquid from the capsule after a predetermined time
- introducing clean water into the capsule and further rotating same to rinse the articles
- pumping the rinsing water from the capsule after a predetermined time

- continuing to pump the capsule so as to lower the pressure therein to below atmospheric for a further predetermined period of time to assist in evaporative drying of the article(s) therein
- removing the article(s) after establishing ambient pressure in the capsule.
- 43. A method as claimed in claim 42, wherein the suction pumping of liquids and air is effected using a venturi suction pump.
- 44. A machine as claimed in any of claims 1 to 41 which includes a reservoir of a volatile cleaning fluid such as isopropyl alcohol, means for introducing the fluid into the capsule with one or more items of clothing or the like which are to be dry cleaned, means for sealing the capsule so as to provide a gas-tight compartment, means for rotating the capsule in the range 80-100rpm, prior to unsealing the capsule to remove the clothing or like articles, and suction pump means, particularly a venturi vacuum pump, for extracting vapours and gases left over from the cleaning process.



(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference		of Transmittal of International Search Report 220) as well as, where applicable, item 5 below.					
KWN 7250-01/H International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)					
PCT/GB 00/01082	23/03/2000	25/03/1999					
Applicant							
NORTH, John Herbert							
This International Search Report has been according to Article 18. A copy is being tra	n prepared by this International Searching Aut ansmitted to the International Bureau.	thority and is transmitted to the applicant					
This International Search Report consists It is also accompanied by	of a total of sheets. a copy of each prior art document cited in this	s report.					
Basis of the report							
a. With regard to the language, the language in which it was filed, un	international search was carried out on the ba less otherwise indicated under this item.	sis of the international application in the					
the international search w Authority (Rule 23.1(b)).	ras carried out on the basis of a translation of	the international application furnished to this					
		ntemational application, the international search					
	onal application in written form.						
filed together with the inte	emational application in computer readable for	m.					
furnished subsequently to	this Authority in written form.						
furnished subsequently to	this Authority in computer readble form.						
the statement that the sui	bsequently furnished written sequence listing on the filed has been furnished.	does not go beyond the disclosure in the					
the statement that the info	ormation recorded in computer readable form	is identical to the written sequence listing has been					
2. Certain claims were fou	nd unsearchable (See Box I).						
3. Unity of invention is lac	king (see Box II).						
4. With regard to the title,							
the text is approved as su	ubmitted by the applicant.						
the text has been establis	shed by this Authority to read as follows:						
5. With regard to the abstract,							
l om	ubmitted by the applicant.						
the text has been established within one month from the	the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.						
6. The figure of the drawings to be pub		19					
as suggested by the app	licant.	None of the figures.					
because the applicant fai	led to suggest a figure.						
because this figure better characterizes the invention.							

International Application No B 00/01082

A. CLASSIFICATION OF SUBJECT MATTER
1PC 7 D06F35/00 D06F43/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) $IPC \ 7 \ D06F$

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUME	NTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to daim No.
Α	WO 97 15709 A (T. PEETERS) 1 May 1997 (1997-05-01)	1-5, 8-11,13, 42
	the whole document	
A	GB 1 069 569 A (CONSTRUCTIEWERKHUIZEN EMILE D'HOOGE P.V.B.A.) the whole document	1,14,18, 37,42
A	US 5 232 476 A (BAXTER INTERNATIONAL INC.) 3 August 1993 (1993-08-03)	1,2, 6-10,13, 42,44
	column 6, line 42 -column 7, line 34; figures 4,5	
	_/ 	

Further documents are listed in the continuation of box C.	Patent family members are listed in annex.		
"A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	 "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family 		
Date of the actual completion of the international search	Date of mailing of the international search report		
3 July 2000	10/07/2000		
Name and mailing address of the ISA	Authorized officer		
European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Courrier, G		

1

International Application No P B 00/01082

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	Delevent to all the No
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 42 36 873 A (H. FALLER) 5 May 1994 (1994-05-05) claims; figures	1-5, 8-11,13, 42
A	US 5 459 945 A (A. SHULENBERGER) 24 October 1995 (1995-10-24) abstract; figures	1,6-8,42
A	US 2 335 560 A (N. CRANE) 30 November 1943 (1943-11-30)	1,2,12, 20,26, 36,42
	the whole document	,

International Application No on patent family members GB 00/01082 Publication Publication Patent family Patent document member(s) date date cited in search report 01-07-1997 BE 1009718 A 01-05-1997 WO 9715709 Α 15-05-1997 7270996 A ΑU 05-01-1966 FR 1412111 A GB 1069569 Α 26-04-1965 NL 6411899 A 21-04-1992 5106404 A 03-08-1993 US US 5232476 Α 05-10-1993 3728893 A ΑU 01-09-1993 MX 9301156 A 13-09-1994 US 5346534 A WO 9317770 A 16-09-1993 23-09-1993 9301373 A ZA 136228 T 15-04-1996 **AT** 25-02-1993 AU 634673 B AU 8613391 A 30-03-1992 BR 9106174 A 16-03-1993 CA 2067163 A 13-03-1992 09-05-1996 DE 69118508 D DE 69118508 T 22-08-1996 DK 498877 T 06-05-1996 EP 0498877 A 19-08-1992 ES 2088017 T 01-08-1996 ΙE 70754 B 30-12-1996 JP 8032289 B 29-03-1996 JP 5500473 T 04-02-1993 MX 9101072 A 04-05-1992 180324 B 23-12-1996 NO 19-03-1992 WO 9204101 A US 5192340 A 09-03-1993 19-04-1994 US 5304253 A

DE 4236873	A	05-05-1994	NONE	
US 5459945	A	24-10-1995	NONE	
US 2335560	Α	30-11-1943	NONE	

ZA

9107047 A

27-05-1992

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 D06F35/00 D06F43/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) IPC 7 D06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the intimational search (name of data base and, where practical, search terms used)

EPO-Internal

	ENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	
A	WO 97 15709 A (T. PEETERS) 1 May 1997 (1997-05-01) the whole document	1-5, 8-11,13, 42	
A	GB 1 069 569 A (CONSTRUCTIEWERKHUIZEN EMILE D'HOOGE P.V.B.A.) the whole document	1,14,18, 37,42	
A	US 5 232 476 A (BAXTER INTERNATIONAL INC.) 3 August 1993 (1993-08-03) column 6, line 42 -column 7, line 34; figures 4,5 -/	1,2, 6-10,13, 42,44	

runner documents are listed in the continuation of box C.	Patent family members are listed in annex.
*Special categories of cited documents: *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family
Date of the actual completion of the international search	Date of mailing of the international search report
3 July 2000	10/07/2000
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer
NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo ni, Fax: (+31–70) 340–3016	Courrier, G

PC176B 00/01082

	tion) DOCUMENTS CONSIDERED TO BE RELEVANT	0/01082		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
A	DE 42 36 873 A (H. FALLER) 5 May 1994 (1994-05-05) claims; figures	1-5, 8-11,13, 42 1,6-8,42		
A	US 5 459 945 A (A. SHULENBERGER) 24 October 1995 (1995-10-24) abstract; figures			
4	US 2 335 560 A (N. CRANE) 30 November 1943 (1943-11-30)	1,2,12, 20,26, 36,42		
	the whole document	36,42		
67				

1

om patent family members

Internal Application No PC 17 GB 00/01082

Patent document cited in search repo	nt	Publication date	Patent family member(s)	Publication date
WO 9715709	Α	01-05-1997	BE 1009718 A	01-07-1997
			AU 7270996 A	15-05-1997
GB 1069569	Α		FR 1412111 A	05-01-1966
	,		NL 6411899 A	26-04-1965
US 5232476	Α	03-08-1993	US 5106404 A	21-04-1992
			AU 3728893 A	05-10-1993
			MX 9301156 A	01-09-1993
			US 5346534 A	13-09-1994
			WO 9317770 A	16-09-1993
			ZA 9301373 A	23-09-1993
			AT 136228 T	15-04-1996
			AU 634673 B	25-02-1993
			AU 8613391 A	30-03-1992
			BR 9106174 A	16-03-1993
			CA 2067163 A	13-03-1992
			DE 69118508 D	09-05-1996
			DE 69118508 T	22-08-1996
			DK 498877 T	06-05-1996
			EP 0498877 A	19-08-1992
			ES 2088017 T	01-08-1996
			IE 70754 B	30-12-1996
			JP 8032289 B	29-03-1996
			JP 5500473 T	04-02-1993
			MX 9101072 A	04-05-1992
			NO 180324 B	23-12-1996
			WO 9204101 A	19-03-1992
			US 5192340 A	09-03-1993
			US 5304253 A	19-04-1994
			ZA 9107047 A	27-05-1992
DE 4236873	Α	05-05-1994	NONE	
US 5459945	A	24-10-1995	NONE	
US 2335560	Α	30-11-1943	NONE	







INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

D06F 35/00, 43/00

A1

(11) International Publication Number: WO 00/58544

(43) International Publication Date: 5 October 2000 (05.10.00)

(21) International Application Number: PCT/GB00/01082

(22) International Filing Date: 23 March 2000 (23.03.00)

(30) Priority Data:
9906800.9
9907304.1
25 March 1999 (25.03.99)
31 March 1999 (31.03.99)
GB

9907304.1 31 March 1999 (31.03.99) GB 9909836.0 29 April 1999 (29.04.99) GB

(71)(72) Applicant and Inventor: NORTH, John, Herbert [GB/GB]; 21 Briar Court, Guardian Road, Norwich NR5 8PR (GB).


(74) Agent: KEITH W. NASH & CO.; 90-92 Regent Street, Cambridge CB2 1DP (GB).

(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: WASHING AND DRYING MACHINES AND DRY-CLEANING MACHINES



(57) Abstract

A machine for washing and/or cleaning articles comprises a sealable enclosure for containing the articles to which cleaning liquid is to be supplied. The cleaning liquid is heated to a high temperature and forced into the enclosure under high pressure as finely dispersed or diffused droplets forming a mist or vapour. A pressure greater than atmospheric is maintained in the enclosure to force the cleaning liquid into at least the surface if not through and into the very structure of the material from which the articles are formed, so as to assist the cleaning process by producing a quicker and more efficient saturation of the articles by the cleaning liquid. The latter may comprise water and detergent or a dry-cleaning solvent. The cleaning liquid is removed from the articles and the interior of the enclosure by means of a suction pump. If a rinse is required, it is replaced by clean liquid for rinsing, preferably also at higher than atmospheric pressure and if desired also heated to higher than ambient temperatures. The rinsing liquid is also removed from the enclosure by suction. The suction is obtained by a suction pump typically a venturi vacuum pump and this is also employed to create a partial vacuum in the enclosure during a drying phase after the cleaning and, if desired rinsing stages.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of Americ
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Кепуа	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

,